

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com

Broughton MCE 3.0



Features

- Nominal 3.0kW cooling duty
- Standard 13amp supply
- EC fans: Greater efficiency, better performance and fully controllable
- Digital thermostatic control
- Low GWP refrigerant R290
- Exhaust up to 1.25m cold air
- IP2X rated
- Made in the UK

Model		MCE 3.0
Cooling Capacity (kW)		3.0
Heating Capacity (kW)		-
Dehumidifying Capacity (l/day)		-
Running Current (amps)	Cooling	3.6
	Heating	-
	Dehumidifying	-
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m³/hr)		520
Fan Speeds		
Operating Range (°c)		18-45°c
Sound Pressure Level (dBA)		50-60
Warm Air Exhaust Duct Diameter / Length (mm/m)		200 / 6
Cold Air Exhaust Duct Diameter (mm)		150mm
Min/Max Umbilical Length (m)		-
Net Weight (kg)		55
Dimensions (H x W x D)	ID Unit (mm)	880 x 400 x 540
	OD Unit (mm)	-
Refrigerant		R290
Condensate Tank Volume (l)		-