

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com

Denso 50HE



Features

- Nominal 17.0kW cooling duty
- 65amp starting current
- Rugged design, proven durability
- Thermostatic control
- 50% RH Operating humidity
- Splashproof (not weatherproof)

Model		50HE
Cooling Capacity (kW)		17.0
Heating Capacity (kW)		-
Dehumidifying Capacity (l/day)		-
Running Current (amps)	Cooling	11.0 (65.0a starting current per phase)
	Heating	-
	Dehumidifying	-
Power Source		400v - 3phase
Flow Volume (m ³ /hr)		2,300
Fan Speeds		2
Operating Range (°c)		20-45°c
Sound Pressure Level ID / OD (dBa)		71
Warm Air Exhaust Duct Diameter / Length (mm/m)		305
Cold Air Exhaust Duct Diameter (mm)		150 / 25m
Min/Max Umbilical Length (m)		-
Net Weight ID / OD (kg)		200
Dimensions (H x W x D)	ID Unit (mm)	1,040 x 1,250 x 800
	OD Unit (mm)	-
Refrigerant		R407C
Condensate Tank Volume (l)		-