

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com



LC KYR-45



Features

- Nominal 4.1kW cooling duty
- 13amp supply
- Works with up to 3m warm air exhaust hose
- 3 speed fan control
- Energy efficient A rated 4.6kW heat pump
- Quiet in operation

Model		KYR-45
Cooling Capacity (kW)		4.1
Heating Capacity (kW)		4.6
Dehumidifying Capacity (l/day)		36
Running Current (amps)	Cooling	8.4
	Heating	8.5
	Dehumidifying	-
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m³/hr)		380
Fan Speeds		3
Operating Range (°c)		17-30°c
Sound Pressure Level ID / OD (dBa)		56
Warm Air Exhaust Duct Diameter / Length (mm/m)		150 / 3
Cold Air Exhaust Duct Diameter (mm)		-
Min/Max Umbilical Length (m)		-
Net Weight ID / OD (kg)		31
Dimensions (H x W x D)	ID Unit (mm)	715 x 440 x 335
	OD Unit (mm)	-
Refrigerant		R290
Condensate Tank Volume (l)		-