

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com

Prem-i-air KY32/D



Features

- Nominal 3.2kW cooling duty
- 13amp supply
- Remote control
- 3 fan speed settings
- Low noise level
- Pump model available for continuous cycle
- Operational electric heater (D model)

Model		KY32 / D
Cooling Capacity (kW)		3.2
Heating Capacity (kW)		- / 2.0
Dehumidifying Capacity (l/day)		53
Running Current (amps)	Cooling	5.2
	Heating	- / 8.9
	Dehumidifying	3.6
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m ³ /hr)		380 / 330
Fan Speeds		3
Operating Range (°c)		16-32°c
Sound Pressure Level ID / OD (dBa)		52
Warm Air Exhaust Duct Diameter / Length (mm/m)		125 / 3
Cold Air Exhaust Duct Diameter (mm)		-
Min/Max Umbilical Length (m)		-
Net Weight ID / OD (kg)		45
Dimensions (H x W x D)	ID Unit (mm)	856 x 450 x 370
	OD Unit (mm)	-
Refrigerant		R407C
Condensate Tank Volume (l)		-