

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com



Simply SP11500AC



Features

- Nominal 3.4kW cooling duty
- 13amp supply
- Digital touch screen
- 24-hour timer
- 3 fan speeds
- Suited to applications up to 23²m
- A rated

Model		SP11500AC
Cooling Capacity (kW)		3.4
Heating Capacity (kW)		-
Dehumidifying Capacity (l/day)		33.6
Running Current (amps)	Cooling	5.8
	Heating	-
	Dehumidifying	-
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m ³ /hr)		410
Fan Speeds		3
Operating Range (°c)		18-32°c
Sound Pressure Level ID / OD (dBa)		65
Warm Air Exhaust Duct Diameter / Length (mm/m)		142 / 1.5
Cold Air Exhaust Duct Diameter (mm)		-
Min/Max Umbilical Length (m)		-
Net Weight ID / OD (kg)		28.5
Dimensions (H x W x D)	ID Unit (mm)	790 x 405 x 420
	OD Unit (mm)	-
Refrigerant		R290
Condensate Tank Volume (l)		-