

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com

Trotec PT 5300 SP



Features

- Nominal 5.3kW cooling duty
- 13amp supply
- Dehumidification function
- Low noise level
- Overheating protection
- Automatic defrost
- IPX0 rated

Model		PT 5300 SP
Cooling Capacity (kW)		5.3
Heating Capacity (kW)		-
Dehumidifying Capacity (l/day)		64.8
Running Current (amps)	Cooling	10.0
	Heating	-
	Dehumidifying	-
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m³/hr)		800
Fan Speeds		2
Operating Range (°c)		18-45°c
Sound Pressure Level ID / OD (dBa)		65
Warm Air Exhaust Duct Diameter / Length (mm/m)		380 / 6
Cold Air Exhaust Duct Diameter (mm)		120 / 2
Min/Max Umbilical Length (m)		-
Net Weight ID / OD (kg)		95
Dimensions (H x W x D)	ID Unit (mm)	1,135 x 560 x 625
	OD Unit (mm)	-
Refrigerant		R1234YF
Condensate Tank Volume (l)		25