

Portable Air Conditioner

Technical Specification



Contact Us

Unit 7 Meadowbrook Industrial Estate
Crawley, West Sussex RH10 9SA

0800 440 444 • 01293 615666 • 0121 359 5100

sales@londoncool.com • mail@midlandcool.com

www.londoncool.com • www.midlandcool.com

Weltem WSC-6000



Features

- Nominal 6.5kW cooling duty
- Digital self-diagnosis function
- Low noise level
- Ergonomic design
- Ideal model for various applications
- Compressor overload protection
- Auto-restart

Model		WSC-6000
Cooling Capacity (kW)		6.5
Heating Capacity (kW)		-
Dehumidifying Capacity (l/day)		-
Running Current (amps)	Cooling	11.9
	Heating	-
	Dehumidifying	-
Power Source		13A - 230v - 50Hz - 1phase
Flow Volume (m ³ /hr)		1,020
Fan Speeds		2
Operating Range (°c)		18-50°C Cooling
Sound Pressure Level ID / OD (dBa)		58
Warm Air Exhaust Duct Diameter / Length (mm/m)		-
Cold Air Exhaust Duct Diameter (mm)		-
Min/Max Umbilical Length (m)		20
Net Weight ID / OD (kg)		93 / 27
Dimensions (H x W x D)	ID Unit (mm)	865 x 705 x 350
	OD Unit (mm)	455 x 665 x 275
Refrigerant		R410a
Condensate Tank Volume (l)		-